# SHIRE 85WB

# 85hp @ 2500rpm







Jacketed dry exhaust manifold



Fuel filter with water drain separator



Туре	John Deere Diesel
Number of Cylinders	4
Displacement	4500 cc
Max HP (ISO 3046/1)	85 hp @ 2500
Electrical System	120 amp 12V alternator
Cooling System	Fresh water cooled with heat exchanger
Gearbox	PRM 280 Hydraulic
Dry Weight (inc gearbox)	545 kg

PRM 280 hydraulic gearbox

### Additional Standard Specification

370 hour engine oil and filter change

Fully dyno tested

Full size replaceable air filter for maximum

filtration and noise reduction

Easy access raw water pump

Easy access to service items from top of engine

(filters, anodes, fuses, water pump)

Morse 33C compatible engine speed and shift control connections

Engine and gearbox sump oil drain pump

Engine extension loom - 2.3 metres

Deluxe control panel, which includes specification of basic panel with additional oil pressure, water temp, gauges and voltmeter

Anti vibration mounts and adjusting screws

Owners handbook

2 and 3D full CAD installation drawings available

Delivered on standard euro pallet

2 Year Warranty on engine and components

1 Year Warranty on all electrical components

## Accessories & Options

Remote coolant header tank	Standard
Engine oil	Standard
Engine coolant / anti-freeze	Standard
Stainless steel water injection exhaust elbow	Standard
Crank mounted stub shaft for PTO (size optional)	Optional
Remote shift control and cables	Optional
Gearbox ratio options	Optional
Flexible fuel line (2 x 1m)	Standard
Diesel fuel filter / water separator	Standard
Flexible output coupling	Optional
Various prop and stern gear components	Optional
Calorifier connections	Optional
24 volt electrics	Optional
PRM 500 gearbox	Optional
Gearbox driven PTO (on PRM 500)	Optional
PK6 crankshaft pulley providing a drive for additional pump, alternator etc.	Optional
Domestic travel power up to 5kW 230V	Optional
Hydraulic drive system	Optional

#### **Deluxe Control Panel**

**Behind The Brands** 



#### **Dimensions**













